

HEINZMANN Configuration Suite

Including driver (PCAN-USB interface, USB to RS-232 converter with FTDI chip, USB to RS-232 converter with Prolific chip) and XML support (German, English), for Windows 7 or higher.

The use of this software product requires availability of the dashboard files compatible with your device.

Revision History

Version 1.1.0

New Window Data Logger

- ▶ New window that enables the configuration for the recording of parameter values (Logging) in the control unit and recording management.

Help file

- ▶ New chapter Data Logger is added

Windows Curve versus Time and X

- ▶ Stop lines can be hidden - useful if pauses occur frequently in recordings
- ▶ Crosshair and zoom function improved

General

- ▶ Expanded port configuration for PHLOX und PHLOX III

Minor bug fix

Updated drivers for dongle

Revision History

Version 1.0.31

Help file

- ▶ Help file has been expanded

Parameter save/load

- ▶ DcDesk allows saving/loading of parameter values only in format *.hzm or *.hzc

Window Curve

- ▶ New curve type is added: polar diagram

CAN communication

- ▶ Correct log out from CAN network in the event of disconnection or loss of network

Changes and additions in various windows

- ▶ Window Dashboard: help function is added
- ▶ Window CAN Device Selection
- ▶ Windows Curve versus time and X

Updated control components