

HEINZMANN Configuration Suite

Including driver (PCAN-USB interface, USB to RS-232 converter with FTDI chip, USB to RS-232 converter with Prolific chip) and XML support (German, English), for Windows 7 or higher.

The use of this software product requires availability of the dashboard files compatible with your device.

Revision History

Version 1.1.2

General optimizations and bug fixes

Version 1.1.0

New Window Data Logger

- ▶ New window that enables the configuration for the recording of parameter values (Logging) in the control unit and recording management.

Help file

- ▶ New chapter Data Logger is added

Windows Curve versus Time and X

- ▶ Stop lines can be hidden - useful if pauses occur frequently in recordings
- ▶ Crosshair and zoom function improved

General

- ▶ Expanded port configuration for PHLOX und PHLOX III

Added new systems: „Cargo Power Display“ and “DynConnect“

Minor bug fix

Revision History

Version 1.0.31

Help file

- ▶ Help file has been expanded

Parameter save/load

- ▶ DcDesk allows saving/loading of parameter values only in format *.hzm or *.hzc

Window Curve

- ▶ New curve type is added: polar diagram

CAN communication

- ▶ Correct log out from CAN network in the event of disconnection or loss of network

Changes and additions in various windows

- ▶ Window Dashboard: help function is added
- ▶ Window CAN Device Selection
- ▶ Windows Curve versus time and X

Updated control components